

The Osburn 1100 stove offers a wide range of possible configurations. It is primarily a freestanding model with pedestal or legs (black, gold or brushed nickel plated) as options, but it can also be easily placed in an alcove or fireplace because its back face is angled at 45°. The top air hood improves heat distribution, regardless of where the stove is installed. The Osburn 1100 burns standard 16" logs and has a burn time of up to five hours in slow combustion mode*. Overall, this versatile and compact wood stove gives a most impressive performance.

1100



1100 on black legs with brushed nickel door

Features

Heating capacity	500 to 1400 sq. ft.*
Firebox volume	1,5 cu. ft.
BTU/hr., EPA test wood	35,000
BTU/hr., seasoned cord wood	50,000
Exterior dimensions	29"H x 23 3/8"W x 23 3/8"D
Maximum log length	16"
Ash drawer with safety lid	Standard
Mobile home approved	Yes**

(See complete technical data on page 25 and 26)

Options

Ultra-quiet 130 CFM blower
Door; painted black, golden fire brown, gold or brushed nickel plated
Pedestal or cast iron legs (painted black, gold or brushed nickel plated)
Adapter for fresh air kit (5" diameter)

* See note 1 on page 26
 ** See note 2 on page 26



1100 on pedestal with black door



1100 on gold legs with gold door