

With its 2.3 cubic foot firebox, the Osburn 2000 insert offers an alternative to the people who love its freestanding counterpart. The two models share the same high quality combustion properties and many of the same features. The Osburn 2000 comes with a standard high-power, heat-activated 130CFM fan strategically positioned to redistribute the heat from the firebox into the room. The 2000 model is designed to receive an optional faceplate that can cover a masonry hearth up to 32 inches (81 cm) high and 50 inches (127 cm) wide. The door overlay is available in black, golden fire brown, gold plated or brushed nickel plated finishes. The faceplate trims are available in black, brassy gold, and nickel.

## 2000 insert

M



Wood inserts

2000 insert with gold door and brassy gold faceplate trims



2000 insert with brushed nickel door and nickel faceplate trims

### Features

Heating capacity	500 to 2100 sq. ft.*
Firebox volume	2,3 cu. ft.
BTU/hr., EPA test wood	49,000
BTU/hr., seasoned cord wood	75,000
Exterior dimensions	22"H x 27"W x 26 1/2"D
Maximum log length	20"
Ultra-quiet 130 CFM blower with variable speed control	Standard

(See complete technical data on page 25 and 26)

### Options

Door; painted black or golden fire brown, or gold or brushed nickel plated  
Faceplate trims ; black, brassy gold or nickel

\* See note 1 on page 26