

The redesigned, improved Saturna direct vent gas insert is back at last! Its flame pattern has been described as one of the most realistic and attractive on the market, and the new firebox panels have been carefully designed to provide a realistic stone fireplace effect. The Saturna's traditional doors are available in a range of different colours including a brand new black nickel-plated finish. The new Saturna gas insert is more than a fire – it's a fire in the true Osburn tradition!

SATURNA

Gas insert



New

	Features
Maximum input (NG)	35,000 BTU
Maximum input (LP)	
Minimum input (NG)	
Minimum input (LP)	
Steady State Efficiency (NG)	
Steady State Efficiency (LP)	64,7%
Tested according to P4 (Canada only) <small>ENERGUIDE</small>	Yes
Variable speed control blower	Standard


(See complete technical data on page 21)

Options

- Decorative doors; painted black, brushed nickel, black nickel or antique brass plated
- Wall thermostat
- Programmable remote control
- Decorative door screen



Features : gas stoves & insert

MODELS	LA30	Romance 28	Britannia 31	West Bay 38	Saturna
Color	Metallic black	Metallic charcoal	Metallic black	Metallic black	Metallic black
Exterior dimensions and weight					
Height	28 1/2"	28"	27 1/8"	29 1/2"	22"
Width	22"	31"	23"	27 1/2"	29 1/2"
Depth	17 1/2"	21 1/4"	15 3/8"	20"	15 1/8"
Weight	175 lbs (80 kg)	247 lbs (112 kg)	155 lbs (71 kg)	200 lbs (90 kg)	110 lbs (50 kg)
Features					
Maximum input (NG / LP)	30,000 / 30,000	28,500 / 26,000	31,000 / 31,000	38,000 / 35,000	35,000 / 35,000
Minimum input (NG / LP)	21,000 / 22,500	19,000 / 20,000	21,000 / 24,000	19,000 / 27,000	17,500 / 17,500
Steady State Efficiency (NG & LP)	72,1%	77,9%	75,3%	76,1%	64,7%
Flue type (direct vent)	Coaxial 4" x 6 5/8"	Coaxial 4" x 6 5/8"	Coaxial 4" x 6 5/8"	Coaxial 4" x 6 5/8"	Dual 3" (Co-Linear)
Approved venting			Dura-Vent, Secure-Vent, Direct-Temp		
Glass type	Ceramic glass	Ceramic glass	Ceramic glass	Ceramic glass	Ceramic glass
Glass viewing area	225 sq. ft.	170 sq. ft.	215 sq. ft.	260 sq. ft.	314 sq. ft.
Burner type	Carbon Steel	Carbon Steel	Stainless Steel	Stainless Steel	Carbon Steel
Valve type	SIT	Honeywell	Honeywell	Honeywell	SIT
B-Vent adaptable	Yes	Yes	Yes	Yes	No
Variable flame control	Yes	Yes	Yes	Yes	Yes
Ceramic fiber log set with glowing embers	Yes	Yes	Yes	Yes	Yes
Approved for installation in a « zero clearance » hearth	N/A	N/A	N/A	N/A	Yes
Mobile home approved	With direct vent	With direct vent	With direct vent	With direct vent	Yes
Alcove approval	No	No	Yes	Yes	N/A
P4 standard (Canada only) 	66,1%	68,9%	66,2%	70,3%	55,0%
Warranty	Lifetime, limited	Lifetime, limited	Lifetime, limited	Lifetime, limited	Lifetime, limited
Security tests	According to CSA, CGA, ANSI, UL and ULC standards applicable in Canada and the United States	According to CSA, CGA, ANSI, UL and ULC standards applicable in Canada and the United States	According to CSA, CGA, ANSI, UL and ULC standards applicable in Canada and the United States	According to CSA, CGA, ANSI, UL and ULC standards applicable in Canada and the United States	According to CSA, CGA, ANSI, UL and ULC standards applicable in Canada and the United States
Clearances to combustible materials					
	Figures 1 and 2, page 23				Figure 3, page 23
1- Side wall	8"	7"	10"	13 1/2"	N/A
2- Back wall	1 1/2"	7"	4"	4"	N/A
3- Corner	1 1/2"	4"	4"	4"	N/A
A- Combustible side wall to unit	N/A	N/A	N/A	N/A	10"
B- Combustible side mantle to unit	N/A	N/A	N/A	N/A	8"
C- Combustible top mantle to unit	N/A	N/A	N/A	N/A	8 1/2"
D- Combustible shelf to unit	N/A	N/A	N/A	N/A	8 1/2" to 14" *
E- Minimum floor protection in front of unit	N/A	N/A	N/A	N/A	0 to 16" **
F, G, H- Minimum hearth dimensions (Height x Width x Depth)	N/A	N/A	N/A	N/A	20 1/2" x 31 1/4" x 15"
Options					
Regular faceplate	N/A	N/A	N/A	N/A	29" x 44"
Large faceplate	N/A	N/A	N/A	N/A	32" x 50"
Faceplate trim kit, black	N/A	N/A	N/A	N/A	Optional
Faceplate trim kit, gold	N/A	N/A	N/A	N/A	Optional
Faceplate trim kit, brushed nickel	N/A	N/A	N/A	N/A	Optional
Decorative door screen	N/A	N/A	N/A	N/A	Optional
Variable speed control blower	Standard	Optional	Standard	Standard	Standard
B-vent adapter	Optional	Optional	Optional	Optional	N/A
Door(s), painted black	Standard	Standard	Optional	Optional	Optional
Door(s), 24K gold plated	N/A	N/A	Optional	Optional	N/A
Door(s), brushed nickel plated	N/A	N/A	Optional	Optional	Optional
Door(s), black nickel plated	N/A	N/A	N/A	N/A	Optional
Door(s), antique brass plated	N/A	N/A	N/A	N/A	Optional
Louver and trivet, painted black	N/A	N/A	Optional	Optional	N/A
Louver and trivet, 24K gold plated	N/A	N/A	Optional	Optional	N/A
Louver and trivet, brushed nickel plated	N/A	N/A	Optional	Optional	N/A
Decorative flue collar, gold or brushed nickel plated	Optional (gold only)	N/A	Optional	Optional	N/A
Programmable remote control	Optional	Optional	Optional	Optional	Optional
Wall thermostat	Optional	Optional	Optional	Optional	Optional

* Depending on the depth of the shelf

** The insert can be installed directly over a combustible floor without floor protection if the insert is at least 5" above the combustible floor.