

The Latest SharkBite® Push-Fit Fittings



DESCRIPTION	SIZE	P/N
Slip Tees	1/2"	U3362
	3/4"	U3370
	1/2" x 1/2" x 1/2" FNPT	U3482
	3/4" x 3/4" x 3/4" FNPT	U3486
Couplings	1/4" x 1/4"	U004
	1/4" x 1/2" FNPT	U066
	5/8" x 5/8"	U012
	3/4" x 5/8"	U057
Bullnose Connectors	3/4" x 1/2" FNPT	U092
	3/4" x 1/2" MNPT	U138
Connectors	1/4" x 1/2" MNPT	U110
	3/4" x 1" MNPT	U139
	5/8" x 3/4" MNPT	U126
Elbows	1/4" x 1/4"	U244
	5/8" x 5/8"	U252
	1/2" x 3/8"	U272
	3/4" x 5/8"	U273
Drop-Ear Elbow	3/4" x 3/4" FNPT	U340
Dishwasher Elbows	1/4" x 3/8" MIP	U276
	1/2" x 3/8" MNPT	U281
Tees	1/4" x 1/4" x 1/4"	U358
	5/8" x 5/8" x 5/8"	U366
	1/2" x 1/2" x 1/4"	U359
End Stop	5/8"	U516
Disconnect Clips	1/4"	U706
	5/8"	U3712
Angle Stop	1/2" x 3/8" compression	23036
Straight Stop	1/2" x 3/8" compression	23037
Stop Valve Tee Adapter	1/4" x 1/4" x 3/8" compression	U3358
Stop Valve Connector	1/4" x 9/16"-24 UNEF thread	U3523
Faucet Connector	1/4" x 1/2" F 14 NPSM threads	U3525
Toilet Connector	1/4" x 7/8" ballcock threads	U3531
Toilet Elbow	1/4" x 7/8" ballcock threads	U3537

Lead Free SharkBite fittings available early 2010. See the SharkBite Catalog for the extended range of Barb fittings, and PEX accessories and tools.

TYPICAL SHARKBITE® APPLICATIONS



Cut. Push. Done. The SharkBite Connection System is the fastest, easiest way to plumb any residential or commercial job. Use for new construction, wet or dry repairs, to connect water heaters and valves, and for hydronic heating systems.

INSTALLATION AND DISCONNECTION



When installing, ensure the pipe is cut square and rough edges and debris are removed. Mark pipe for 1" depth. Push pipe and fitting together. Use the disconnect clip or tongs to easily change or reuse a SharkBite fitting.



CERTIFICATIONS

The SharkBite® push-fit fittings have been design certified and listed to ASSE 1061/NSF 61. The SharkBite® push-fit fittings are listed by IAPMO and are certified for potable and hydronic heating water distribution (note: Glycol mixture for hydronics is not to exceed 50% concentration). The SharkBite® push-fit fittings have been certified for underground applications and as a manufactured joint without access panels and they meet UPC, IPC and cUPC requirements.

Please consult with local plumbing codes concerning specific applications.

The SharkBite® tubing without oxygen barrier is approved for all model codes in the US and Canada for use in hydronic and potable water systems and is certified to the following standards: NSF 14/61, NSF P171, ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904. The SharkBite® tubing with oxygen barrier is approved for use in all model codes in the US and Canada for use in hydronic and potable water systems and is certified to the following standards: NSF 14/61, NSF P171, ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904.

Lead-Free Fittings are Lead-Free per HSC116875.

SHARKBITE® PEX INSIDE (ID) & OUTSIDE DIAMETER (OD)

Nominal Diameter	OD inches	ID inches
3/8"	0.5	0.35
1/2"	0.625	0.475
3/4"	0.875	0.671
1"	1.125	0.885




OVERBUILT IS AN UNDERSTATEMENT.®

2400 7th Avenue SW • Cullman, AL 35055-0278
1-877-700-4242 • FAX: 1-877-700-4280
www.cashacme.com

In Canada Contact:

1-888-820-0120 • FAX: 1-888-820-0121
www.cashacme.ca

A Division of the Reliance Worldwide Corporation 





THE SHARKBITE® CONNECTION SYSTEM

LIGHTNING FAST. WON'T LET GO.

- Connects Copper, CPVC and PEX pipe in any combination.
- No soldering, clamps, unions or glue.
- Certified to 200 psi and 200°F.
- Approved for use underground and behind walls without access panels.
- Certified for potable water and hydronics.
- Integral tube liner for PEX installations.
- Fittings can even be rotated after assembly for easier installation in tight spaces.
- Easy to disconnect if needed.



SHARKBITE® PUSH-FIT PRODUCTS

(Available in 1/4" through 1" sizes)

FITTINGS AND MANIFOLDS

Straight Couplings
Reducing Couplings
Straight Connectors
Reducing Connectors
Elbows (reducing, drop-ear & hy-ear)
End Stops
Tees (regular, reducing & bullnose)
Reducers & Adapters
Slip Couplings & Slip Tees
Manifolds with SharkBite Push-fit Branches
Fixture Supply Fittings

VALVES (with integral and union connectors)

Pressure Regulating
Thermostatic Mixing Valves
Check Valves
Ball Valves
Retrofit Tailpiece Kits
Chrome Plated Stops

OTHER PRODUCTS

Pressure Gauges
Temperature Gauges
Water Hammer Arrestors
Flexible Water Heater Connectors
Bypass Kits
Water Heater Kit
Contractor Kit
Irrigation Contractor Kit

TOOLS

Safe Seal Tool
Disconnect Clips
Disconnect Tongs



Only the SharkBite Connection System offers the Total Rough-In Solution™—the fastest way from meter to fixtures. For complete details visit sharkbite.com or call 1-877-700-4242.



SHARKBITE® BARB PRODUCTS

(Available in 3/8" through 1" sizes)

FITTINGS AND MANIFOLDS

Couplings
Reducing Couplings
Sweat Adapters
Threaded Adapters
Elbows (regular, reducing & drop-ear)
Tees (regular & reducing)
Copper Barb Manifolds
Copper Stubout Elbow
Clamp & Crimp Rings
Swivel Fittings

VALVES

Ball & Regulator (with PEX/Barb Ends)
Chrome Plated Stops

BRACKETS

Bend Supports
Suspension Clamps and Insulators

TOOLS

Clamp Tools
Crimp Tools & Kits
Crimp Ring Gauge
PEX Tubing Cutter



SHARKBITE® PEX TUBING

For residential and commercial plumbing applications.

5', 10' and 20' straight lengths, plus 25', 50', 100', 300', 500' and 1000' coils. Sizes 1/4" through 1".

Without Oxygen Barrier for water distribution systems.

With Oxygen Barrier for hydronic heating applications.

